

THE WRIGHT WAY TO MOW

WRIGHT COMMERCIAL MOWERS



PERFECTING THE ART OF PRODUCTIVITY

From revolutionary stand-on mowers to rugged walk-behinds, Wright is the choice of professionals everywhere.

In 1997, the first Wright Stander® rolled off the assembly line in Gaithersburg, Maryland. And the mowing industry was changed forever.

The original Stander introduced new levels of agility and control to lawn maintenance professionals, and elevated productivity like no other machine. From its revolutionary stand-on design and patented zero-turn radius to its precision-crafted components, the Wright Stander had no equal—which still holds true today.

We offer a full range of mowers that maximize your productivity under any conditions. Our Standers continue to be the benchmark for stand-on performance and quality, while our

mid-mount Z's deliver power and speed to handle your largest jobs. The Sport™ model gives you the option to sit or stand, and our Velke® walk-behinds provide reliability and convenience in a traditional design. And all models have compact footprints so that you can fit more mowers on a trailer.

Ultimately, Wright knows that the only thing that's as pleasing to the eye as a perfectly cut lawn is a healthy profit. We invite you to learn why our mowers help deliver both on the following pages, at www.wrightmfg.com, or at your nearest Wright dealer. More than ever, you'll see why Wright is the **Stander of Excellence.**

**WRIGHT STANDERS ARE MORE THAN STAND-ON
MOWERS. THEY ARE AN EXPRESSION OF THE
VISION AND COMMITMENT OF AN INDUSTRY
INNOVATOR AND LEADER. WRIGHT CREATED THE
STAND-ON CATEGORY AND WE'VE BEEN PERFECTING
IT EVER SINCE. TODAY WE'RE PROUD TO CONTINUE
DEVELOPING MOWING TECHNOLOGY THAT RESULTS
IN MASTERWORKS OF PRODUCTIVITY, RELIABILITY
AND OPERATOR COMFORT.**





Stander I Specs

MODEL	DECK SIZE	ENGINE	LENGTH	WIDTH*	DRY WEIGHT
WSTN36FS600E	36"	18.5 HP Kawasaki FS600 ELEC	62"	36.5"	726 lbs
WSTN36FX600E	36"	19.0 HP Kawasaki FX600 ELEC HD AC	62"	36.5"	726 lbs
WSTN48FX600E	48"	19.0 HP Kawasaki FX600 ELEC HD AC	59.75"	49"	815 lbs
WSTN48FX691E	48"	22.0 HP Kawasaki FX691 ELEC HD AC	59.75"	49"	815 lbs
WSTN52FX600E	52"	19.0 HP Kawasaki FX600 ELEC HD AC	59.75"	53"	823 lbs
WSTN52FX691E	52"	22.0 HP Kawasaki FX691 ELEC HD AC	59.75"	53"	823 lbs

A MASTERPIECE OF MOWING TECHNOLOGY

STANDER INTENSITY

The Stander Intensity™ takes extra-compact stand-on mowing to a whole new level. It's versatile enough to take on big jobs as well as fit in tight spaces, and has outstanding weight distribution for handling hills. Its free-floating AERO CORE™ deck delivers unparalleled cut quality in any mowing environment. And its floating foot platform with elastopolymer bumpers absorbs rough terrain for a smooth, comfortable ride. The Intensity is the perfect look for improving your productivity.

It's **everything you need** to get
the **productivity you want.**



Mower

- Cutting height range 1" - 5"
- Adjustable deck lift in .25" increments
- Deck construction 7 gauge
- Blades .25" high-lift wing
 - 36" - two blades 18"
 - 48" - three blades 16.5"
 - 52" - three blades 18"
- Blade tip speed at 3584 rpm
- Warner™ blade clutch/brake 125 ft. lbs.
- Sealed ball bearing spindles 1" shaft & ductile iron housing
- Side & mulch discharge system

Tractor

- Quad-Lever™ operator controls with ball bearings
- Hydro-Gear® hydro pumps 10 cc
- Hydro-Gear® wheel motors 12 cu in
- Fuel capacity 5.5 gallons
- Drive tires
 - 18 x 8.5 - 10 (36")
 - 18 x 10.5 - 10 (48" and 52")
- Flat free caster tires 11 x 4 - 5
- Forward speed 8.0 mph
- Reverse speed 3.5 mph

* Add 13" with deflector

INSPIRING EVERYWHERE YOU LOOK

STANDER X

If you're looking for the ultimate in stand-on mowing technology, your search ends here. The Stander X™ features Wright's unparalleled zero-turn radius maneuverability and class-leading ground speed. Its powerful AERO CORE™ deck has a unique flow design that pulls more grass upright so that the blades can cut them evenly. And anti-clumping baffles prevent debris build-up at discharge. Furthermore, cut height can be adjusted quickly and precisely. In every inch of the Stander X, you'll find a stroke of genius.



You can do **more work** in less time
with **better results** than ever before.

Stander X Specs

MODEL	DECK SIZE	ENGINE	LENGTH	WIDTH*	DRY WEIGHT
WSTX48FX691E	48"	22.0 HP Kawasaki FX691 ELEC HD AC	61.375"	49"	930 lbs
WSTX52FX691E	52"	22.0 HP Kawasaki FX691 ELEC HD AC	62"	53"	940 lbs
WSTX52FX730E	52"	23.5 HP Kawasaki FX730 ELEC HD AC	62"	53"	940 lbs
WSTX52ECV740E	52"	24.5 HP Kohler ECV740 ELEC HD AC	62"	53"	945 lbs
WSTX61FX730E	61"	23.5 HP Kawasaki FX730 ELEC HD AC	64.375"	62"	1010 lbs
WSTX61ECV740E	61"	24.5 HP Kohler ECV740 ELEC HD AC	64.375"	62"	1015 lbs



Mower

- Cutting height range 1.5" - 5"
- Adjustable deck lift in .25" increments
- Deck construction 7 gauge
- Blades .25" high-lift wing
 - 48" - three blades 16.5"
 - 52" - three blades 18"
 - 61" - three blades 21"
- Blade tip speed at 3584 rpm
- Warner™ blade clutch/brake 200 ft. lbs.
- Sealed ball bearing spindles 1" shaft & ductile iron housing
- Side & mulch discharge system

Tractor

- Quad-Lever™ operator controls with ball bearings
- Hydro-Gear® hydro pumps 12 cc with cooling fans
- Hydro-Gear® wheel motors 15 cu in
- Fuel capacity 5.5 gallons
- Drive tires 20 x 10 - 8
- Flat free caster tires 13 x 5 - 6
- Forward speed 9.5 mph
- Reverse speed 5.5 mph

* Add 12" with deflector





Building the highest quality mowers in the industry.

At Wright, we believe there is only one way to create a professional mower—without compromise. Not only without compromise to quality, but also to efficiency, value and the environment as well.

Every model is assembled at our state-of-the-art production facility and headquarters in Frederick, Maryland. We don't have satellite plants or factories scattered around the country, so we maintain optimal quality control at all times. We employ just-in-time production methods to increase efficiency while lowering costs—and passing the savings on to you.



Stander ZK Specs

MODEL	DECK SIZE	ENGINE	LENGTH	WIDTH*	DRY WEIGHT
WSZK52FX801E	52"	25.5 HP Kawasaki FX801 ELEC HD AC	67.5"	53"	1200 lbs
WSZK52FX850E-49S	52"	27.0 HP Kawasaki FX850 49S ELEC HD AC	67.5"	53"	1200 lbs
WSZK52FX801E	61"	25.5 HP Kawasaki FX801 ELEC HD AC	69"	62"	1270 lbs
WSZK52FX850E-49S	61"	27.0 HP Kawasaki FX850 49S ELEC HD AC	69"	62"	1270 lbs

A PORTRAIT IN HIGH PERFORMANCE

THE STANDER ZK

From any viewpoint, the Stander ZK™ is an awe-inspiring display of pure mowing prowess. You get the horsepower to handle massive jobs, as well as the agility and stability only a Wright Stander delivers. The ZK also features a low center of gravity and large tires for excellent hillside stability, and Quick Cut™ height adjustment so it mows more lawns in the same time as any comparable mid-mount Z. It's a must-see for any professional seeking a machine that can do it all.

It makes bigger jobs smaller –
and my job easier.



Mower

- Cutting height range 1.5" - 5.5"
- Adjustable deck lift in .25" increments
- Deck construction 7 gauge
- Blades .25" high-lift wing
 - 52" - three blades 18"
 - 61" - three blades 21"
- Blade tip speed 3584 rpm
- Warner™ blade clutch/brake 200 ft. lbs.
- Sealed ball bearing spindles 1" shaft & ductile iron housing
- Side & mulch discharge system

Tractor

- Quad-Lever™ operator controls with ball bearings
- Hydro-Gear® hydro pumps 16 cc with cooling fans
- Hydro-Gear® wheel motors 15 cu in
- Fuel capacity 17.5 gallons
- Drive tires
 - 24 x 9.5 - 12 (52")
 - 24 x 12 - 12 (61")
- Flat free caster tires 13 x 6.5 - 6
- Forward speed 13.5 mph
- Reverse speed 7.0 mph

THE ORIGINAL THAT STARTED A MOVEMENT

STANDER

The stand-on mowing revolution started right here. However, today's Stander® is even more refined, agile and well balanced than its forefather. The patented stand-on design, known as Operator Balance Control (OBC), lets you become an extension of the machine which allows you to handle changing terrain and hills almost as fast as level ground.

Navigating tight spaces is a breeze with the Stander's zero-turn radius capability. And the compact size means it will never have to be left off the trailer. Even now, the Stander is still making a bold statement in mowing performance.



It eliminates the obstacles that
stand in the way of productivity.

Large and Small Frame Fixed Deck Stander Specs

MODEL	DECK SIZE	ENGINE	LENGTH	WIDTH*	DRY WEIGHT
WS32FS541R	32"	15.0 HP Kawasaki FS541 REC	58"	33.5"	635 lbs
WS32FS600RE	32"	18.5 HP Kawasaki FS600 REC/ELEC	58"	33.5"	635 lbs
WS36FS541R	36"	15.0 HP Kawasaki FS541 REC	60"	36.5"	645 lbs
WS36FS600RE	36"	18.5 HP Kawasaki FS600 REC/ELEC	60"	36.5"	645 lbs
WS42FS600RE	42"	18.5 HP Kawasaki FS600 REC/ELEC	63"	24.5"	655 lbs
WS48FS600RE	48"	18.5 HP Kawasaki FS600 REC/ELEC	59.25"	49"	850 lbs
WS48FX600E	48"	19.0 HP Kawasaki FX600 ELEC HD AC	59.25"	49"	850 lbs
WS48FX691E	48"	22.0 HP Kawasaki FX691 ELEC HD AC	59.25"	49"	850 lbs
WS52FX600E	52"	19.0 HP Kawasaki FX600 ELEC HD AC	59.875"	53"	870 lbs
WS52FX691E	52"	22.0 HP Kawasaki FX691 ELEC HD AC	59.875"	53"	870 lbs
WS52FX730E	52"	23.5 HP Kawasaki FX730 ELEC HD AC	59.875"	53"	870 lbs
WS61FX691E	61"	22.0 HP Kawasaki FX691 ELEC HD AC	62.5"	62"	1010 lbs
WS61FX730E	61"	23.5 HP Kawasaki FX730 ELEC HD AC	62.5"	62"	1010 lbs



Mower

- Cutting height range
1.75" - 4.5" (32", 36" and 42")
1.25" - 5.0" (48", 52" and 61")
- Deck construction 7 gauge
- Blades .25" high-lift wing
32" - two blades 16.5"
36" - two blades 18"
42" - two blades 21"
48" - three blades 16.5"
52" - three blades 18"
61" - three blades 21"
- AERO CORE™ deck on 48", 52" and 61"
- Caster shims
- Blade tip speed at 3584 rpm
19,000 fpm
- Warner™ blade clutch/brake
125 ft. lbs. (32", 36" and 42")
200 ft. lbs. (48", 52" and 61")
- Sealed ball bearing spindles 1" shaft & ductile iron housing
- Side & mulch discharge system

Tractor

- Quad-Lever™ operator controls with ball bearings on 48", 52" and 61"
- Hydro-Gear® hydro pumps
10 cc (32", 36" and 42")
12 cc with cooling fans (48", 52" and 61")
- Hydro-Gear® wheel motors
12 cu in (32", 36" and 42")
15 cu in (48", 52" and 61")
- Drive tires
18 x 6.5 - 8 (32")
18 x 8.5 - 8 (36" and 42")
20 x 10 - 8 (48", 52" and 61")
- Flat free caster tires
11 x 4.0 - 5 (32", 36" and 42")
13 x 5.0 - 6 (48", 52" and 61")
- Forward speed
7.5 mph (32", 36" and 42")
9.5 mph (48", 52" and 61")
- Reverse speed
4.3 mph (32", 36" and 42")
5.5 mph (48", 52" and 61")





**At Wright, the best way
is the only way.**

Our facility features the latest manufacturing technologies and techniques, as well as dedicated metal cutting, welding and fabricating divisions. This ensures that every component and system in our mowers is precision-crafted. We also employ an eco-friendly powder coating process, and maintain an exceptionally clean work environment.



Sport X Specs

MODEL	DECK SIZE	ENGINE	LENGTH	WIDTH*	DRY WEIGHT
WSPX48FX691E	48"	22.0 HP Kawasaki FX691 ELEC HD AC	61.375"	49"	970 lbs
WSPX52FX691E	52"	22.0 HP Kawasaki FX691 ELEC HD AC	62"	53"	990 lbs
WSPX52FX730E	52"	23.5 HP Kawasaki FX730 ELEC HD AC	62"	53"	990 lbs
WSPX52ECV740E	52"	24.5 HP Kohler ECV740 ELEC HD AC	62"	53"	995 lbs
WSPX61FX730E	61"	23.5 HP Kawasaki FX730 ELEC HD AC	64.375"	62"	1050 lbs
WSPX52ECV740E	61"	24.5 HP Kohler ECV740 ELEC HD AC	64.375"	62"	1055 lbs

AN EXPRESSION OF SPEED AND AGILITY

SPORT X

Master the art of mowing in virtually any environment with the Wright Sport X™. Its compact footprint and streamlined saddle profile lets you sit or stand to navigate tight spaces. Yet its powerful engine options and light weight deliver the speed you need to quickly finish off open areas. And its floating AERO CORE™ deck provides a smooth, even cut over hills and varying terrain. Get the eye-opening results you want on every job with the Sport X.

You gain the freedom to position yourself perfectly
in any mowing environment.



Mower

- Cutting height range 1.5" - 5"
- Adjustable deck lift in .25" increments
- Deck construction 7 gauge
- Blades .25" high-lift wing
 - 48" - three blades 16.5"
 - 52" - three blades 18"
 - 61" - three blades 21"
- Blade tip speed at 3584 rpm
- 19,000 fpm
- Warner™ blade clutch/brake
- 200 ft. lbs.
- Sealed ball bearing spindles 1"
- shaft & ductile iron housing
- Side & mulch discharge system

Tractor

- Quad-Lever™ operator controls with ball bearings
- Hydro-Gear® hydro pumps 12 cc with cooling fans
- Hydro-Gear® wheel motors 15 cu in
- Fuel capacity 5.5 gallons
- Drive tires 20 x 10 - 8
- Flat free caster tires 13 x 5 - 6
- Forward speed 9.5 mph
- Reverse speed 5.5 mph

WHERE FORM FOLLOWS FUNCTION

SPORT RH

The Sport RH™ delivers the same lightweight, compact design as our Sport X model for handling tight spaces. Plus it has a convenient rapid height adjustment feature so you can cut different types of grass, on smooth or variable terrain, with complete confidence. A single, easy-grip lever allows adjustments in precise 0.25" increments. In any landscape, the Sport RH puts you in total control.

The standing or sitting position provides
maximum operator balance and control.



Sport RH Specs

MODEL	DECK SIZE	ENGINE	LENGTH	WIDTH*	DRY WEIGHT
WSES36FS600RE	36"	18.5 HP Kawasaki FS600 REC/ELEC	63"	36.5"	765 lbs
WSES36FX600E	36"	19.0 HP Kawasaki FX600 ELEC HD AC	63"	36.5"	765 lbs
WSES42FS600RE	42"	18.5 HP Kawasaki FS600 REC/ELEC	66"	42.5"	780 lbs
WSES42FX600E	42"	19.0 HP Kawasaki FX600 ELEC HD AC	66"	42.5"	780 lbs
WSES48FX600E	48"	19.0 HP Kawasaki FX600 ELEC HD AC	58.5"	49"	880 lbs
WSES52FX600E	52"	19.0 HP Kawasaki FX600 ELEC HD AC	59.5"	53"	890 lbs



Mower

- Cutting height range 1" - 5"
- Adjustable deck lift in .25" increments
- Deck construction 7 gauge
- Blades .25" high-lift wing
 - 36" - two blades 18"
 - 42" - two blades 21"
 - 48" - three blades 16.5"
 - 52" - three blades 18"
- Blade tip speed at 3584 rpm
- 19,000 fpm
- Warner™ blade clutch/brake
 - 125 ft. lbs.
- Sealed ball bearing spindles 1" shaft & ductile iron housing
- Side & mulch discharge system

Tractor

- Quad-Lever™ operator controls
- Hydro-Gear® hydro pumps 10 cc
- Hydro-Gear® wheel motors 12 cu in
- Fuel capacity 5.5 gallons
- Drive tires
 - 18 x 8.0 - 10 (36" and 42")
 - 18 x 10.5 - 10 (48" and 52")
- Flat free caster tires 11 x 4.0 - 5
- Forward speed 7.5 mph
- Reverse speed 4.3 mph

* Add 12" with deflector





**We follow a standard
beyond any other.**

Wright's engineering teams are among the most innovative in the commercial lawn maintenance industry, with over 40 patents received. In addition, Wright is a member of the Maryland World Class Manufacturing Consortium, an organization dedicated to promoting and advancing best practices in manufacturing. We are regularly asked by the State of Maryland to give tours of our facility to other Maryland-based companies who seek to improve their manufacturing operations.



Wright Z Specs

MODEL	DECK SIZE	ENGINE	LENGTH	WIDTH*	DRY WEIGHT
WZ48FX801E	48"	25.5 HP Kawasaki FX801 ELEC HD AC	78"	49"	1190 lbs
WZ52FX801E	52"	25.5 HP Kawasaki FX801 ELEC HD AC	78"	53"	1210 lbs
WZ52FX850E-49S	52"	27.0 HP Kawasaki FX850 49S ELEC HD AC	78"	53"	1210 lbs
WZ61FX801E	61"	25.5 HP Kawasaki FX801 ELEC HD AC	78"	62"	1240 lbs
WZ52FX850E-49S	61"	27.0 HP Kawasaki FX850 49S ELEC HD AC	78"	62"	1240 lbs

TIMELESS POWER AND PRODUCTIVITY

WRIGHT Z

Sometimes there's just no substitute for horsepower and speed on extra large jobs. With the Wright Z™, you also don't have to sacrifice a high quality cut for muscle to get the job done quickly and efficiently. Yet it also features a compact, lightweight design that fits easily on a trailer and reduces rut damage on soft turf. And the low center of gravity gives you the stability to handle hills and maneuver around obstacles with confidence.

Large hydro pumps let the mid-mount Z **run faster** and **cooler than the competition.**



Mower

- Cutting height range 1.5" - 5.5"
- Adjustable deck lift in .25" increments
- Deck construction 7 gauge
- Blades .25" high-lift wing
 - 48" - three blades 16.5"
 - 52" - three blades 18"
 - 61" - three blades 21"
- Blade tip speed at 3584 rpm
19,000 fpm
- Warner™ blade clutch/brake
200 ft. lbs.
- Sealed ball bearing spindles 1"
shaft & ductile iron housing
- Side & mulch discharge system
- Adjustable suspension seat

Tractor

- Hydro-Gear® hydro pumps 16 cc
- Hydro-Gear® wheel motors 15 cu in
- Fuel capacity 15 gallons
- Drive tires
 - 24 x 9.5 - 12 (48" and 52")
 - 24 x 12 - 12 (61")
- Flat free caster tires
 - 13 x 5 - 6 (48" and 52")
 - 13 x 6.5 - 6 (61")
- Forward speed 13 mph
- Reverse speed 7.0 mph

THE PICTURE OF STRENGTH AND SPEED

WRIGHT ZTO

Mid-mount technology is fully optimized in the Wright ZTO™. The large transaxles make the ZTO strong, fast and light—and the most agile mid-mount Z in its class. The ZTO also includes a host of smart features such as an integrated parking brake that engages when levers are opened, and an undercarriage cage to protect the transmissions and filters.



Handles your **biggest, toughest jobs**
without **breaking a sweat or stride.**

Wright ZTO Specs

MODEL	DECK SIZE	ENGINE	LENGTH	WIDTH*	DRY WEIGHT
WZT048FX691E	48"	22.0 HP Kawasaki FX691 ELEC HD AC	78"	49"	1090 lbs
WZT04826BSE (J1940)	48"	26.0 HP Briggs 26BS ELEC CYCL AC	78"	49"	1090 lbs
WZT052FX691E	52"	22.0 HP Kawasaki FX691 ELEC HD AC	78"	53"	1100 lbs
WZT052FX730E	52"	23.5 HP Kawasaki FX730 ELEC HD AC	78"	53"	1100 lbs
WZT05226BSE (J1940)	52"	26.0 HP Briggs 26BS ELEC CYCL AC	78"	53"	1100 lbs
WZT061FX730E	61"	23.5 HP Kawasaki FX730 ELEC HD AC	78"	62"	1160 lbs



Mower

- Cutting height range 1.5" - 5.5"
- Adjustable deck lift in .25" increments
- Deck construction 7 gauge
- Blades .25" high-lift wing
 - 48" - three blades 16.5"
 - 52" - three blades 18"
 - 61" - three blades 21"
- Blade tip speed at 3584 rpm
- 19,000 fpm
- Warner™ blade clutch/brake 200 ft. lbs.
- Sealed ball bearing spindles 1" shaft & ductile iron housing
- Side & mulch discharge system

Tractor

- Fuel capacity 14.5 gallons
- Hydro-Gear® 3400 series hydro transmissions
- Drive tires 23 x 10.5 - 12
- Flat free caster tires 13 x 5.0 - 6
- Forward speed 10.5 mph
- Reverse speed 4.0 mph



Velke Hydro and Gear Drive Specs

MODEL	DECK SIZE	ENGINE	LENGTH	WIDTH*	DRY WEIGHT
WVH32FS541R	32"	15.0 HP Kawasaki FS541 REC	72"	33.5"	540 lbs
WVH36FS541R	36"	15.0 HP Kawasaki FS541 REC	74"	36.5"	560 lbs
WVH36FS600RE	36"	18.5 HP Kawasaki FS600 REC/ELEC	74"	36.5"	560 lbs
WVH48FS600RE	48"	18.5 HP Kawasaki FS600 REC/ELEC	69"	49"	690 lbs
WVH52FS600RE	52"	18.5 HP Kawasaki FS600 REC/ELEC	71.5"	53"	720 lbs
WVG32FS541R	32"	15.0 HP Kawasaki FS541 REC	74"	33.5"	480 lbs
WVG36FS541R	36"	15.0 HP Kawasaki FS541 REC	79"	36.5"	520 lbs
WVG48FS541R	48"	15.0 HP Kawasaki FS541 REC	70"	49"	560 lbs

BEAUTIFULLY RELIABLE ON ANY JOB

VELKE HYDRO

A rugged, simple design is often what you want most in a walk-behind mower.

The Velke® Hydro™ has fewer components than its competitors—which means greater reliability and, ultimately, cost savings. Available with pistol-grip controls, a compact footprint, and the largest drive tires of any fixed-deck walk-behind in the industry, the Velke Hydro is the complete package.



VELKE GEAR DRIVE

A classic design that also offers extraordinary durability—that's the Velke Gear Drive™ walk-behind. It provides a superior cut in a simple, compact package you can depend on season after season. The Velke Gear Drive also comes with a rock-solid 5-speed transmission and is specifically designed for use with an array of sulky accessories for greater operator comfort.



Mowers

- Cutting height range 1" - 4.25"
- Deck construction 7 gauge
- Blades .25" high-lift wing
 - 32" - two blades 16.5"
 - 36" - two blades 18"
 - 48" - three blades 16.5"
 - 52" - three blades 18" (Hydro Only)
- Caster shims
- Deck adjustment

- Blade tip speed at 3584 rpm
19,000 fpm
- Warner™ blade clutch/brake
125 ft. lbs.
- Sealed ball bearing spindles 1"
shaft & ductile iron housing
- Side & mulch discharge system

Tractors

- Pistol grip operator controls
- Fuel capacity 5.5 gallons
- Flat free caster tires 9 x 3.5 - 4

Tractor – Hydro

- Hydro-Gear® hydro pumps 10 cc
- Hydro-Gear® wheel motors 12 cu in
- Drive tires
 - 16 x 4.0 - 8 (32")
 - 18 x 6.5 - 8 (36")
 - 18 x 8.5 - 8 (48" and 52")
- Forward speed
 - 6.5 mph (32")
 - 7.2 mph (36", 48" and 52")
- Reverse speed
 - 3.9 mph (32")
 - 4.3 mph (36", 48" and 52")

Tractor – Gear Drive

- Peerless™ 5-speed with reverse
- Dual belt drive
- Drive tires
 - 13 x 5 - 6 (32")
 - 13 x 6.5 - 6 (36" and 48")
- Forward speed 4.5 mph
- Reverse speed 1 – 3 mph

DECK AND ENGINE SPECIFICATIONS

	Stander Small Frame	Stander I	Stander X	Stander Large Frame	Stander ZK
Mower					
Cutting Height	1.25" - 5"	1" - 5"	1.5" - 5"	1.25" - 5"	1.5" - 5.5"
Deck Lift System	Caster Shims	Quick Cut™ (.25")	Quick Cut™ (.25")	Caster Shims	Quick Cut™ (.25")
Deck Construction	7 Gauge	7 Gauge	7 Gauge	7 Gauge	7 Gauge
Blades	2	2 or 3	3	3	3
Blade Tip Speed at 3,584 rpm	19,000 fpm	19,000 fpm	19,000 fpm	19,000 fpm	19,000 fpm
Spindles	Ductile iron housing, Sealed bearing	Ductile iron housing, Sealed bearing	Ductile iron housing, Sealed bearing	Ductile iron housing, Sealed bearing	Ductile iron housing, Sealed bearing
Spindle Shaft	1"	1"	1"	1"	1"
Blade Clutch Brake	125 ft. lbs.	125 ft. lbs.	200 ft. lbs.	200 ft. lbs.	200 ft. lbs.
Discharge	Side, Mulch & Rear	Side & Mulch	Side & Mulch	Side & Mulch	Side & Mulch
Engine – Horsepower					
32" Mower Deck	Kawasaki 15.0 & 18.5	n/a	n/a	n/a	n/a
36" Mower Deck	Kawasaki 15.0 & 18.5	Kawasaki 18.5 & 19.0	n/a	n/a	n/a
42" Mower Deck	n/a	n/a	n/a	n/a	n/a
48" Mower Deck	n/a	Kawasaki 19.0 & 22.0	Kawasaki 22.0	Kawasaki 19.0 & 22.0	n/a
52" Mower Deck	n/a	Kawasaki 19.0 & 22.0	Kawasaki 22.0 & 23.5	Kawasaki 19.0, 22.0 & 23.5	Kawasaki 25.5 & 27.0
52" Mower Deck	n/a	Kawasaki 19.0 & 22.0	Kohler EFI 24.6	Kohler EFI 24.6	n/a
61" Mower Deck	n/a	n/a	Kawasaki 23.5	Kawasaki 23.5	Kawasaki 25.5 & 27.0
61" Mower Deck	n/a	n/a	Kohler EFI 24.6	Kohler EFI 24.6	n/a
Starting	Recoil & Electric	Recoil & Electric	Electric	Electric	Electric
Tractor					
Operating Controls	Quad-Lever™	Quad-Lever™	Quad-Lever™	Quad-Lever™	Quad-Lever™
Hydro Pumps	Hydro-Gear® 10 cc	Hydro-Gear® 10 cc	Hydro-Gear® 12 cc	Hydro-Gear® 12 cc	Hydro-Gear® 16 cc
Wheel Motors	Hydro-Gear® 12 cu. in.	Hydro-Gear® 12 cu. in.	Hydro-Gear® 15 cu. in.	Hydro-Gear® 15 cu. in.	Hydro-Gear® 15 cu. in.
Fuel Capacity	5.5 Gallons	5.5 Gallons	5.5 Gallons	5.5 Gallons	17.5 Gallons
Drive Tires					
32" Mower Deck	18 x 6.5 - 8 (4 Ply)	n/a	n/a	n/a	n/a
36" Mower Deck	18 x 8.5 - 8 (4 Ply)	18 x 8.5 - 10	n/a	n/a	n/a
42" Mower Deck	18 x 8.5 - 8 (4 Ply)	n/a	n/a	n/a	n/a
48" Mower Deck	n/a	18 x 10.5 - 10	20 x 10 - 8 (4 Ply)	20 x 10 - 8 (4 Ply)	n/a
52" Mower Deck	n/a	18 x 10.5 - 10	20 x 10 - 8 (4 Ply)	20 x 10 - 8 (4 Ply)	24" x 9.5" - 12 (4-Ply)
61" Mower Deck	n/a	n/a	20 x 10 - 8 (4 Ply)	20 x 10 - 8 (4 Ply)	24" x 12" - 12 (4-Ply)
Caster Tires – Flat Free					
32" Mower Deck	11 x 4.0 - 5	n/a	n/a	n/a	n/a
36" Mower Deck	11 x 4.0 - 5	11 x 4.0 - 5	n/a	n/a	n/a
42" Mower Deck	11 x 4.0 - 5	n/a	n/a	n/a	n/a
48" Mower Deck	n/a	11 x 4.0 - 5	13 x 5.0 - 6	13 x 5.0 - 6	n/a
52" Mower Deck	n/a	11 x 4.0 - 5	13 x 5.0 - 6	13 x 5.0 - 6	13 x 6.5 - 6
61" Mower Deck	n/a	n/a	13 x 5.0 - 6	13 x 5.0 - 6	13 x 6.5 - 6
Speed					
Speed Forward (MPH)	7.5	8.0	9.5	9.5	13.5
Speed Reverse (MPH)	4.3	3.5	5.5	5.5	7.0
Overall Length					
32" Mower Deck	58"	n/a	n/a	n/a	n/a
36" Mower Deck	60"	62"	n/a	n/a	n/a
42" Mower Deck	63"	n/a	n/a	n/a	n/a
48" Mower Deck	n/a	59.75"	61.375"	59.25"	n/a
52" Mower Deck	n/a	59.75"	62"	59.875"	67.5"
61" Mower Deck	n/a	n/a	64.375"	62.5"	69"
Width – Deflector Up (Down)					
32" Mower Deck	33.5" (45.5")	n/a	n/a	n/a	n/a
36" Mower Deck	36.5" (48.5")	36.5" (49.5")	n/a	n/a	n/a
42" Mower Deck	42.5" (54.5")	n/a	n/a	n/a	n/a
48" Mower Deck	n/a	49" (62")	49" (61")	49" (61")	n/a
52" Mower Deck	n/a	53" (66")	53" (65")	53" (65")	53" (65")
61" Mower Deck	n/a	n/a	62" (74")	62" (74")	62" (74")
Dry Weight (lbs.)					
32" Mower Deck	635	n/a	n/a	n/a	n/a
36" Mower Deck	645	726	n/a	n/a	n/a
42" Mower Deck	680	n/a	n/a	n/a	n/a
48" Mower Deck	n/a	815	930	850	n/a
52" Mower Deck	n/a	823	940	870	1200
61" Mower Deck	n/a	n/a	1010	943	1270

	Sport RH	Sport X	Wright Z	Wright ZTO	Velke Hydro	Velke Gear Drive
Mower						
Cutting Height	1.0" - 5"	1.5" - 5"	1.5" - 5.5"	1.5" - 5.5"	1" - 4.25"	1" - 4.25"
Deck Lift System	Quick Cut™ (.25")	Quick Cut™ (.25")	Foot Pedal (.25")	Foot Pedal (.25")	Caster Shims	Caster Shims
Deck Construction	7 Gauge	7 Gauge	7 Gauge	7 Gauge	7 Gauge	7 Gauge
Blades	2 or 3	3	3	3	2 or 3	2 or 3
Blade Tip Speed at 3,584 rpm	19,000 fpm	19,000 fpm	19,000 fpm	19,000 fpm	19,000 fpm	19,000 fpm
Spindles	Ductile iron housing, Sealed bearing	Ductile iron housing, Sealed bearing	Ductile iron housing, Sealed bearing	Ductile iron housing, Sealed bearing	Ductile iron housing, Sealed bearing	Ductile iron housing, Sealed bearing
Spindle Shaft	1"	1"	1"	1"	1"	1"
Blade Clutch Brake	125 ft. lbs.	200 ft. lbs.	200 ft. lbs.	200 ft. lbs.	125 ft. lbs.	125 ft. lbs.
Discharge	Side, Mulch & Rear	Side & Mulch	Side & Mulch	Side & Mulch	Side & Mulch	Side & Mulch
Engine – Horsepower						
32" Mower Deck	n/a	n/a	n/a	n/a	Kawasaki 15.0	Kawasaki 15.0
36" Mower Deck	Kawasaki 18.5 & 19.0	n/a	n/a	n/a	Kawasaki 15.0 & 18.5	Kawasaki 15.0
42" Mower Deck	Kawasaki 18.5 & 19.0	n/a	n/a	n/a	n/a	n/a
48" Mower Deck	Kawasaki 19.0	Kawasaki 22.0	Kawasaki 25.5	Kawasaki 22.0	Kawasaki 18.5	Kawasaki 15.0
48" Mower Deck	n/a	n/a	n/a	Briggs & Stratton 26.0	n/a	n/a
52" Mower Deck	Kawasaki 19.0	Kawasaki 22.0 & 23.5	Kawasaki 25.5 & 27.0	Kawasaki 22.0 & 23.5	Kawasaki 18.5	n/a
52" Mower Deck	n/a	Kohler EFI 24.6	n/a	n/a	n/a	n/a
52" Mower Deck	n/a	n/a	n/a	Briggs & Stratton 26.0	n/a	n/a
61" Mower Deck	n/a	Kawasaki 23.5	Kawasaki 25.5 & 27.0	Kawasaki 23.5	n/a	n/a
61" Mower Deck	n/a	Kohler EFI 24.6	n/a	n/a	n/a	n/a
61" Mower Deck	n/a	n/a	n/a	Briggs & Stratton 26.0	n/a	n/a
Starting	Recoil & Electric	Electric	Electric	Electric	Recoil & Electric	Recoil
Tractor						
Operating Controls	Quad-Lever™	Quad-Lever™	Over Lap Levers	Over Lap Levers	Pistol Grips	Pistol Grips
Hydro Pumps	Hydro-Gear® 10 cc	Hydro-Gear® 12 cc	Hydro-Gear® 16 cc	Hydro-Gear®	Hydro-Gear® 10 cc	Peerless™
Wheel Motors	Hydro-Gear® 12 cu. in.	Hydro-Gear® 15 cu. in.	Hydro-Gear® 15 cu. in.	3400 Series Transmissions	Hydro-Gear® 12 cu. in.	5 - Speed w/reverse
Fuel Capacity	5.5 Gallons	5.5 Gallons	14.5 Gallons	14.5 Gallons	5.5 Gallons	5.5 Gallons
Drive Tires						
32" Mower Deck	n/a	n/a	n/a	n/a	16 x 4.0 - 8 (4 Ply)	13 x 5 - 6 (4 Ply)
36" Mower Deck	18 x 8.0 - 10 (4 Ply)	n/a	n/a	n/a	18 x 6.5 - 8 (4 Ply)	13 x 6.5 - 6 (4 Ply)
42" Mower Deck	18 x 8.0 - 10 (4 Ply)	n/a	n/a	n/a	18 x 8.5 - 8 (4 Ply)	n/a
48" Mower Deck	18 x 10.5 - 10 (4 Ply)	20 x 10 - 8 (4 Ply)	24 x 9.5 - 12 (4 Ply)	23 x 10.5 - 12	18 x 8.5 - 8 (4 Ply)	13 x 6.5 - 6 (4 Ply)
52" Mower Deck	18 x 10.5 - 10 (4 Ply)	20 x 10 - 8 (4 Ply)	24 x 9.5 - 12 (4 Ply)	23 x 10.5 - 12	18 x 8.5 - 8 (4 Ply)	n/a
61" Mower Deck	n/a	20 x 10 - 8 (4 Ply)	24 x 12 - 12 (4 Ply)	23 x 10.5 - 12	n/a	n/a
Caster Tires – Flat Free						
32" Mower Deck	n/a	n/a	n/a	n/a	9 x 3.5 - 4	9 x 3.5 - 4
36" Mower Deck	11 x 4.0 - 5	n/a	n/a	n/a	9 x 3.5 - 4	9 x 3.5 - 4
42" Mower Deck	11 x 4.0 - 5	n/a	n/a	n/a	9 x 3.5 - 4	n/a
48" Mower Deck	11 x 4.0 - 5	13 x 5.0 - 6	13 x 5.0 - 6	13 x 5.0 - 6	9 x 3.5 - 4	9 x 3.5 - 4
52" Mower Deck	11 x 4.0 - 5	13 x 5.0 - 6	13 x 5.0 - 6	13 x 5.0 - 6	9 x 3.5 - 4	n/a
61" Mower Deck	n/a	13 x 5.0 - 6	13 x 6.5 - 6	13 x 5.0 - 6	n/a	n/a
Speed						
Speed Forward (MPH)	7.5	9.5	13.0	10.5	6.5 (32"), 7.5	4.5
Speed Reverse (MPH)	4.3	5.5	7.0	4.0	3.9 (32"), 4.3	1.0 - 3.0
Overall Length						
32" Mower Deck	n/a	n/a	n/a	n/a	72"	74"
36" Mower Deck	63"	n/a	n/a	n/a	74"	79"
42" Mower Deck	66"	n/a	n/a	n/a	n/a	n/a
48" Mower Deck	58.5"	61.375"	78"	78"	69"	70"
52" Mower Deck	59.5"	62"	78"	78"	71.5"	n/a
61" Mower Deck	n/a	64.375"	78"	78"	n/a	n/a
Width – Deflector Up (Down)						
32" Mower Deck	n/a	n/a	n/a	n/a	33.5" (45.5")	33.5" (45.5")
36" Mower Deck	36.5" (48.5")	n/a	n/a	n/a	36.5" (48.5")	36.5" (48.5")
42" Mower Deck	42.5" (54.5")	n/a	n/a	n/a	n/a	n/a
48" Mower Deck	49" (61")	49" (61")	49" (61")	49" (61")	49" (61")	49" (61")
52" Mower Deck	53" (65")	53" (65")	53" (65")	53" (65")	53" (65")	n/a
61" Mower Deck	n/a	62" (74")	62" (74")	62" (74")	n/a	n/a
Dry Weight (lbs.)						
32" Mower Deck	n/a	n/a	n/a	n/a	540	480
36" Mower Deck	765	n/a	n/a	n/a	560	520
42" Mower Deck	780	n/a	n/a	n/a	n/a	n/a
48" Mower Deck	880	816	1190	1015	690	560
52" Mower Deck	890	890	1210	1025	720	n/a
61" Mower Deck	n/a	943	1240	1060	n/a	n/a

THE FINISHING TOUCHES

RIDE-BEHIND ACCESSORIES

Velke sulkies give operators a smoother, more comfortable ride, and help increase productivity. Each is engineered to work on Wright models as well as other professional mower brands.



VELKE SULKY™

- Increases comfort and productivity
- Patented design keeps you closer to handles and away from obstacles on zero turns
- Strong welded steel construction
- Fits most professional brands
- Operator capacity of approximately 200 lbs.



VELKE X2™ SULKY

Same great features as the Velke Sulky, plus:

- Wide, open platform for greater operator comfort
- The only two wheel sulky available today
- Operator capacity of approximately 280 lbs.

GRASS COLLECTION ACCESSORIES

Our grass collection accessories are built to stand up to hard use season after season. They're engineered to fit Wright mowers as well as other professional brands.



GRASS GOBBLER™

- Designed for continuous airflow and high-density packing
- Durable all steel construction
- Available in small (2.0 cu. ft.), regular (3.3 cu. ft.), jumbo (4.3 cu. ft.), Turbo 4 (4.6 cu. ft.) and Turbo 10 (4.8 cu. ft.) capacities
- Fits most professional brands



POWERED GRASS COLLECTION SYSTEM

- Designed specifically for Wright Z and ZTO models
- Holds up to 8 bushels for 48" models, 12 bushels for 61" models, and your choice of 8 or 12 bushel systems for 52" models
- Rear wheel motors can be moved fore and aft to maintain proper weight balance

EVERYBODY. EVERYDAY.

Building mowers. Building teams. Building companies. Building lives.

4600 Wedgewood Boulevard, Suite X
Frederick, MD 21703

301.360.9810

301.360.9820 Fax

www.wrightmfg.com

THE WRIGHT WAY TO MOW

wright[™]
commercial products